

Data sheet

Drying Oven SLW 53 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART PRO controller:


- large (7"), clear, full colour touch screen
- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download


TECHNICAL DATA		
air convection	forced	
chamber capacity [I] /1/	56	
working capacity [I]	56	
controller	microprocessor with external LCD graphic display	
display	7" full colour touch screen	
TEMPERATURE		
temperature range [°C]	+5°C above ambient temperature +300°C	
temperature resolution every [°C]	0,1	
over temperature protection	class 3.1 to DIN 12880	

POL-EKO-APARATURA sp.j. Your partner in laboratory analysis and technological processes

кD

CHAMBER		
door type	solid / door with viewing window (option)	
interior		
Smart PRO	acid-proof stainless steel to DIN 1.4301	
IG Smart PRO	acid-proof stainless steel to DIN 1.4301	
housing		
Smart PRO	powder coated sheet	
IG Smart PRO	stainless steel linen finish	
overall dims [mm] /2/		
width A	590	
height B	700	
depth C	620	
internal dims [mm]		
width D	400	
height E	390	
depth F	360	





shelves (standard / max)	2 // 5
max shelf workload [kg] /5/	25
- reinforced shelf version (PW) /3/	50
max unit workload [kg]	40
- reinforced unit version (W) /4/	80
weight [kg]	50
ELECTRICAL PARAMETERS	
voltage*	230V 50Hz
nominal power [W]	1700
warranty	24 months
manufacturer	POL-EKO-APARATURA

all the above technical data refer to standard units (without optional accessories)

* - 230V 60Hz, 115V 60Hz also available

1 - working capacity of chamber can be smaller

2 - depth doesn't include 50 mm of power cable
3 - reinforced shelf
4 - reinforced version

5 - on uniformly loaded surface

POL-EKO-APARATURA sp.j.

Your partner in laboratory analysis and technological processes



OPTIONS AND ACCESSORIES

	COORTED	
	Order number: */A	Door with viewing window
	Order number: */P INOX	Stainless steel wire shelf
	Order number: */PP	Perforated shelf
	Order number: */PW	Reinforced shelf
\Diamond	Order number: KUW GN*/*	Stainless steel cuvettes
Ø	Order number: QLK*	Wheels
₽.	Order number: */S or */S INOX	Table with wheels
₽	Order number: */ST or */S INOX	Table with wheels
KG	Order number: */W	Reinforced version
	Order number: OWW/OWW LED	Interior lighting
•	Order number: PT 100	Additional temperature sensor
HEPA	Order number: HEPA	HEPA - fresh air filter
$(\mathbf{)}$	Order number: OCZ/N	Non-standard access port for external sensor
LAB DESK	Order numberLabDesk	LabDesk - software
٩	Order number: BRT/*/L or IQ/OQ/PQ	Calibration and IQ, OQ, PQ qualification