

Chiller with air-cooled refrigerating unit and circulation pump (stainless steel). Housing, atmospheric open expansion tank and copper soldered evaporator made of stainless steel. With digital level indicator. For externally closed applications.

Pilot ONE:

The new Pilot ONE controller with pioneering technology and advanced control functions brings numerous advantages to routine work. The extensive features list includes a brilliant 5,7" TFT touchscreen display, USB and network connections, an integrated technical glossary and language support in 13 languages (EN, DE, FR, IT, ES, RU, CN, PT, JP, CZ, PL, KO, TR). The Pilot ONE has a convenient navigation system with easily remembered icons and menu categories which are colour sorted to make routine work simpler. Thanks to a favourites menu and One-Click operator guidance all important information is always just a few keystrokes away. Software wizards also help you to set up, ensuring correct settings. The USB port allows connection of the system to a PC or notebook. Together with the Spy software, requirements such as remote control or data transmission are easily achieved in a cost-effective manner. Network integration is easy with the internet port.

The range of functions can be expanded very easily via E-grade at any time by entering a unit specific upgrade code:

E-grade "Exclusive": TAC (True Adaptive Control) - self optimising internal and cascade control, selectable temperature control mode (Internal/Process), programmer with 3 programs (max. 15 steps), ramp function (linear), 5 point calibration, scalable graphic display, favourites menu, display resolution 0,01 K.

E-grade "Professional": Programmer with 10 programs (max. 100 steps), ramp function for temperature gradients (linear and non-linear), 2nd set point, user menus (Administrator level), calendar start.

3-2-2 warranty - registration required.

Technical data according to DIN 12876

Operating temperature range	-20...40 °C
temperature set point / display	5,7" colour Touchscreen
Internal temperature sensor	Pt100
Sensor external connection	Pt100
Temperature stability at -10°C	0,5 K
Interface digital	Ethernet, USB (Host u. Device), RS232
Safety classification	Class I / NFL
Cooling power at ambient temperature +20°C	.
at 20°C	7,5 kW
at 0°C	6,1 kW
at -10°C	4 kW
at -20°C	2,4 kW
Refrigeration machine	air-cooled, CFC- and HCFC-free
Refrigerant	R449A
Refrigerant quantity	1,035 kg
Circulation pump:	E1
max. delivery	48 l/min
max. delivery pressure	3,4 bar
Delivery at 0,3 bar	46 l/min
Delivery at 0,5 bar	44 l/min
Delivery at 1,0 bar	40 l/min
Delivery at 1,5 bar	33 l/min
Delivery at 2,0 bar	27 l/min
Delivery at 2,5 bar	20 l/min
Delivery at 3,0 bar	11 l/min
Pump connection	G1 1/4 male
min. filling capacity	18 l
Volume of expansion	48 l
Overall dimensions WxDxH **	740x1160x1050 mm
Net weight	295 kg
sound pressure level +/- 4 dB(A)	61 dB(A)
Power supply (3 Phase)	400V 3~ 50Hz *
max. current (3 Phase)	7,5 A
Fuse (3 phase)	3x10 A
Degree of Protection	IP20



Order-No.: 3040.0031.01

Technical data according to DIN 12876

min. ambient temperature	5 °C
max. ambient temperature	40 °C

from Serial-No.:

1.0/20

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.

Included Accessories:

mini-USB cable #54949, Hose coupling for G1 1/4 male, , cover expansion tank,

Optional accessories:

Com.G@te, POKO/ECS interface, temperature control / - connection hoses, thermofluids, further accessories, etc.: see catalog.

Output data valid for: Room temperature 20° C. If the ambient temperature rises, the cooling capacity may drop.

in accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%

Example -5% voltage and + 2% frequency -> not allowed!

-5% voltage and - 2% frequency -> allowed

Information to Electromagnetic compatibility:

Classification (disturbance) to EN55011: Class A, Group 1

Standard delivery conditions - Power cable configuration:

1. Single-phase devices (230V/115V) -> with cable and plug
2. Three-phase devices with current consumption less than 63A -> with cable, without plug
3. Three-phase devices with current consumption greater than 63A -> without cable, without plug

This unit is US-SNAP and applicable EU law compliant.

** Please respect space requirements. See operating conditions at www.huber-online.com