

## Multi Reax

P/N: 545-10000-00



The all-purpose model

- Unique shaker to accommodate up to 26 vessels with various diameters. Shipment includes as a standard: Attachment for 26 vessels with diameters from 10 to 16 mm  
Attachment for 12 vessels with diameters from 16 to 32 mm
- The 3-mm vibration orbit allows for excellent mixing results in large and solid samples
- Set and continuously adjust the variable speeds from 150 to 2,000 rpm on the digital display
- A digital process timer allows for unattended operation and can be set from 1 to 999 minutes. When the set time has elapsed, an acoustic alarm will sound and the operation stops

## Multi Reax - Technical Data

Overheat protection	self-resetting
Permissible ambient conditions	5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity
Weight	9.8 kg
Protection class DIN EN 60529	IP 30
Timer	Yes
Rotation speed range	150 - 2,000 rpm
Power input	50 W
Dimensions (w/d/h)	270 x 410 x 172 mm
Max. Load	1.5 kg
Operating Mode	timer or continuous
Rotation speed setting	digital
Orbit / Stroke	3 mm
Platform size	-
Accessories included	2 carousel attachments
Angle	-
Motion	vibrating