



NF200

Bench Top Centrifuge



- Compact design for separation of blood samples, urine particle sedimentation and other routine applications in emergency and small laboratories
- N-Prime™ programmable microprocessor control system for accurate and reliable operations
- Easy programming with one button, just turn and push
- Two large LED displays for speed/RCF and time
- Possibility of programming RCF
- Pulse key for short centrifugation requirements
- Reduced temperature increase in the chamber by means of continuous air cooling through air channel in the lid
- Quiet brushless induction drive
- Safety ensured by steel body, lid and chamber, lid locking system and motor over temperature protection
- Delivered with 12x15 ml. angle rotor

N-prime

TECHNICAL SPECIFICATIONS

Maximum Speed	5.000 rpm
Maximum RCF	2.822xg
Tube Capacity	12x15 ml.
Control System	N-Prime™ Programmable Microprocessor Control
Speed Set Range	1.000-5.000 rpm
Speed Set Step	10 rpm
Timer Set Range	1-99 Minutes and Hold Position
Timer Set Step	1 minute
Motor	Induction Motor
Body, Lid and Chamber	Epoxy-Polyester Powder Coated Steel
Power Supply	230 V / 50-60 Hz (115 V / 60 Hz)
Power Consumption	150 W
External Dimensions (WxDxH) mm.	280x360x260
Packing Dimensions (WxDxH) mm.	350x420x480
Net / Packed Weight, kg.	12 / 16

ROTOR

Rotor Type	Capacity	Max. Tube Dia. (mm)	Radius (mm)	Max. Speed	Max. RCF
Angle	12x15 ml.	17	101	5.000 rpm	2.822xg

ADAPTORS

Code	Tube Type	Max. Tube Dia. (mm)
G 03 057	1.5/2 ml tubes	11
G 03 014	7 ml vacuumed/ non vacuumed tubes	13
G 03 015	5 ml vacuumed/ non vacuumed tubes	13



NUVE SANAYİ MALZEMELERİ İMALAT VE TİCARET A.Ş.

Saracalar Mah. Saracalar Kümevleri No: 4/2 Akyurt 06750 ANKARA / TURKEY t. +90 312 399 28 30 f. +90 312 399 21 97
nuve.com.tr sales@nuve.com.tr

ISO 9001: 2008
ISO 13485: 2003 