

Chiller with water-cooled refrigerating unit and circulation pump (stainless steel). Housing, atmospheric open expansion tank and copper soldered evaporator made of stainless steel. With digital level indicator. For externally closed applications.

Pilot ONE:

The new Pilot ONE controller with pioneering technology and advanced control functions brings numerous advantages to routine work. The extensive features list includes a brilliant 5,7" TFT touchscreen display, USB and network connections, an integrated technical glossary and language support in 13 languages (EN, DE, FR, IT, ES, RU, CN, PT, JP, CZ, PL, KO, TR). The Pilot ONE has a convenient navigation system with easily remembered icons and menu categories which are colour sorted to make routine work simpler. Thanks to a favourites menu and One-Click operator guidance all important information is always just a few keystrokes away. Software wizards also help you to set up, ensuring correct settings. The USB port allows connection of the system to a PC or notebook. Together with the Spy software, requirements such as remote control or data transmission are easily achieved in a cost-effective manner. Network integration is easy with the internet port.

The range of functions can be expanded very easily via E-grade at any time by entering a unit specific upgrade code:

E-grade "Exclusive": TAC (True Adaptive Control) - self optimising internal and cascade control, selectable temperature control mode (Internal/Process), programmer with 3 programs (max. 15 steps), ramp function (linear), 5 point calibration, scalable graphic display, favourites menu, display resolution 0,01 K.

E-grade "Professional": Programmer with 10 programs (max. 100 steps), ramp function for temperature gradients (linear and non-linear), 2nd set point, user menus (Administrator level), calendar start.

3-2-2 warranty - registration required.

Technical data according to DIN 12876

Operating temperature range	-20...40 °C
temperature set point / display	5,7" colour Touchscreen
Internal temperature sensor	Pt100
Sensor external connection	Pt100
Temperature stability at -10°C	0,5 K
Interface digital	Ethernet, USB (Host u. Device), RS232
Safety classification	Class I / NFL
Cooling power	
at 15°C	10 kW
at 0°C	10 kW
at -10°C	6,5 kW
at -20°C	3 kW
Refrigeration machine	water-cooled, CFC- and HCFC-free
Refrigerant	R449A
Refrigerant quantity	1,75 kg
Circulation pump	C3
max. delivery	96 l/min
max. delivery pressure	5,6 bar
Delivery at 0,5 bar	92 l/min
Delivery at 1,0 bar	86 l/min
Delivery at 1,5 bar	81 l/min
Delivery at 2,0 bar	75 l/min
Delivery at 2,5 bar	68 l/min
Delivery at 3,0 bar	62 l/min
Delivery at 3,5 bar	54 l/min
Delivery at 4,0 bar	46 l/min
Delivery at 4,5 bar	37 l/min
Delivery at 5,0 bar	24 l/min
Pump connection	G1 1/4 male
Cooling water connection	G1/2 male
Consumption at water 15°C, flow 15°C	510 l/h
Consumption at water 15°C, flow 0°C	510 l/h
Consumption at water 15°C, flow -10°C	375 l/h
Consumption at water 15°C, flow -20°C	276 l/h
min. cooling water differential pressure	1 bar



Order-No.: 3017.0040.01

Technical data according to DIN 12876

max. cooling water pressure	6 bar
min. filling capacity	6,5 l
Volume of expansion	5,5 l
Overall dimensions WxDxH **	600x600x1450 mm
Net weight	230 kg
sound pressure level +/- 4 dB(A)	72 dB(A)
Power supply (3 Phase)	400V 3~ 50Hz *
max. current (3 Phase)	12 A
Fuse (3 phase)	3x16 A
Degree of Protection	IP20
min. ambient temperature	5 °C
max. ambient temperature	40 °C

from Serial-No.:

1.0/20

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.

Accessories and periphery: mini-USB cable #54949*, Hose coupling for G1 1/4 male*, hose coupling cooling water for G1/2 male*, cover expansion tank*, connection tubes, braided hoses for cooling water, external sensor, connecting cable

* standard equipment

Output data valid for: Room temperature 20°C, cooling water inlet 15°C and 1 bar differential pressure between cooling water inlet and - outlet. This temperature control unit has been designed to operate with cooling water up to 20°C. As the cooling water temperature increases, drop in the cooling power should be expected, and also an increased cooling water flow rate possible. Materials used in the cooling water circuit include: copper, Stainless steel 1.4401, MS, PA, PPE, PTFE and EPDM. Please use suitable cooling water.

in accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%

Example -5% voltage and + 2% frequency -> not allowed!

-5% voltage and - 2% frequency -> allowed

Information to Electromagnetic compatibility:

Classification (disturbance) to EN55011: Class A, Group 1

Standard delivery conditions - Power cable configuration:

1. Single-phase devices (230V/115V) -> with cable and plug
2. Three-phase devices with current consumption less than 63A -> with cable, without plug
3. Three-phase devices with current consumption greater than 63A -> without cable, without plug

This unit is US-SNAP and applicable EU law compliant.

** Please respect space requirements. See operating conditions at www.huber-online.com